

POSI-PLUS LINERUNNER 800 CABLE PLACER

WITH 40' OF WORKING HEIGHT, CDL & NON-CDL CONFIGURATIONS



SPECS

WORKING HEIGHT: 40'

REEL LIFTERS: 5000# & 8000#

SIDE REACH: 29'

PLATFORM SIZE: 29X29X42"

PLATFORM CAPACITY: 500 LBS.

SIDE-PULL CAPACITY: 600 LBS.

CABLE DOWN LOAD CAPACITY: 150 LBS.

BOOM LIFTING EYE CAPACITY: 2,000 LBS.

TRAVEL HEIGHT: 11'

BOOM ARTICULATION: -20 - +80 DEGREES

MINIMUM GVWR: 22,950-33,000 LBS.

AVAILABLE ON MANY DIFFERENT CHASSIS MAKES, MODELS

SUPERIOR FLEXIBILITY:

SIMPLIFIED AND OPTIMIZED CONTROL SYSTEM USING CAN-BUS TECHNOLOGYY

FULLY FEATHERABLE AND ADJUSTABLE CONTROLS

EASILY INTERCHANGEABLE CONTROLS

ON-SCREEN DIAGNOSTICS AND TROUBLESHOOTING

USER-FRIENDLY CONTROLS (BACK LITE PICTOGRAMS)

USER-FRIENDLY MAINTENANCE AND TROUBLESHOOTING

CUSTOMIZABLE JOYSTICK CONFIGURATION

SMART STRINGING SYSTEM:

VERSATILE AND SAFE STRINGING ROUTING

FASTER TOW LINE WINCH, FULLY FEATHERABLE AND SELF-LOCKING FOR HEAVY WORK

EFFICIENT CABLE TENSIONING CONTROL

SUPERIOR CAPABILITY:

SMART FLOW SHARING BASED ON FLOW, PRESSURE, TEMPERATURE AND DEMAND

CUSTOMIZABLE ADJUSTABLE SPEED (ON-SCREEN PROGRAMMABLE)

SMART ENERGY MANAGEMENT

THE BEST LIFE CYCLE COST EFFECTIVENESS

SUPERIOR ERGONOMICS & SAFETY:

INNOVATIVE VISUAL COMMUNICATION SYSTEM

THE BEST ERGONOMIC DESIGN ON THE MARKET

THE BEST CAPACITY PERFORMANCES ON THE MARKET

THE MOST COMPACT AND VERSATILE PLACER ON THE MARKET

SUPERIOR FEATHERABILITY







888-925-0858 www.customtruck.com



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.