



IMT 42684 HYDRAULIC LOADER

AVAILABLE ON VARIOUS MAKES OF CHASSIS



SPECS

CRANE RATING: 305,580 FT-LB (42.25 TM)

HORIZONTAL REACH: 82' 10" (25.25 M)

VERTICAL REACH: 93' 6" (28.51 M)

MAX. LIFT CAPACITY: 10,500 LB (4763 KG)

LIFTING HEIGHT: 94' 5" (28.77 M)

HYDRAULIC EXTENSION: 20' 3" (6.168 M) 34' 6" (10.51 M)

OPERATING WEIGHT: 13,201 LB (5988 KG)

CRANE STORAGE HEIGHT: 13' 6" (4.12 M)

MOUNTING SPACE: 41" (1.1 M)

ROTATIONAL TORQUE: 48,678 FT-LB (6.73 TM)

ROTATION: 420°

STANDARD FEATURES

UP TO 82' 10" (25.25 M) OF HORIZONTAL REACH

RADIO REMOTE WITH INFOCENTER

OIL COOLER

ROTATION SYSTEM

420 DEGREE TURNTABLE BEARING POWERED BY DUAL HYDRAULIC MOTORS

HEAVY-DUTY GEARBOX EQUIPPED WITH A HEAT TREATED PINION

OVERLOAD SYSTEM

ELECTRONIC RATED CAPACITY LIMITATION (RCL) 5300 BLOCKS LOAD-INCREASING



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

