



TEREX GENERAL 65 DIGGER DERRICK

WITH 65.1' SHEAVE HEIGHT



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com



**CUSTOM
TRUCK**
ONE SOURCE™

TEREX GENERAL 65 DIGGER DERRICK

WITH 65.1' SHEAVE HEIGHT

EQUIPMENT SPECS

LIFTING CAPACITY: 42,110 LBS.
CAPACITY @ 10': 21,010 LBS.
MAX SHEAVE HEIGHT: 65.1'
MAX. LOAD RADIUS: 9.7'
MAX. HORIZONTAL REACH: 55.1'
MAX. DIGGING RADIUS: 36.4'
100 DEGREES OF BOOM TRAVEL (+80 TO -20)
DUAL LIFT CYLINDERS
SELF-ALIGNING SWIVEL BALL BUSHINGS
RECTANGULAR, BI-AXIAL EPOXY RESIN,
FILAMENT WOUND FIBERGLASS BOOMS
BOX FABRICATED STEEL LOWER & INTERMEDIATE BOOM
HYDRAULIC BOOM EXTENSION -
INTERMEDIATE & UPPER
FULL PRESSURE HYDRAULIC CONTROLS
FULL PRESSURE HYDRAULIC SYSTEM, OPEN-CENTER
70 GALLON HYDRAULIC OIL RESERVOIR
CUSTOM MADE/ZONED LOAD CHART
CONTINUOUS UNRESTRICTED ROTATION
15,000LB. PLANETARY TURNTABLE WINCH
PLANETARY PARKING BRAKE ROTATION
RIGHT-HAND COMMAND POST CONTROLS
ENGINE STOP / START @ LOWER CONTROLS
BOOM ANGLE INDICATOR
OUTRIGGER INTERLOCK
MOVING OUTRIGGER ALARM
AVAILABLE ON MANY DIFFERENT CHASSIS MAKES, MODELS



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com